

## DIGITAL INTERFACE BOARD WITH FOUR INPUT PORTS

<sup>1</sup> TIRIAN Gelu Ovidiu

<sup>1</sup> THE UNIVERSITY "POLITEHNICA" TIMISOARA,  
THE FACULTY OF ENGINEERING HUNEDOARA


### Summary:

This work presents a digital interface board with four 8-byte input ports to be connected to the ISA bus of the computer. The 4 ports can be addressable anywhere in the address space of the port by using the 3 jumpers.

**Key words:** digital interface, input ports, bus, jumpers.

### 1. INTRODUCTION

The digital interface board with four 8-byte input ports has been created in didactic scope.



**Fig. 1.** The block diagram


The block diagram of the board is described in Fig. 1 and contains the selector block implemented by 4 BCD decimal decoders, as well as the input circuits block that has 4 output circuits.

These two blocks are connected to the address, data and control buses, as follows:

- a) The input circuits block to the data buses ( SD<sub>0</sub>- SD<sub>7</sub>)
- b) The port selection block to the address buses (SA<sub>0</sub>- SA<sub>9</sub>) and to the control buses ( AEN, IORC, IOWC).

**2. THE SYNTHESIS OF THE DECODER**

The decoders can be defined as demultiplexer circuits for which the input is at logic level 1 I= 1 (+V). In this case, according to the Boolean operation that describes the action of the DEMUX, the circuit becomes a code identifier. This is realized because each output will identify one of the input operations. Therefore, the decoders can be represented as a block diagram like in Fig. 2.



*Fig. 2. The block diagram*

Let N be the binary number expressed by the input combination and M the binary number expressed by the output combination. Thus, it can be written:


$$M = 2^N$$

As one can notice, the expression obtained is an inverse function of the function realized by the decoder, for which the encoding outputs were obtained as  $M = \log_2 N$ .

The decoders can also be found as an M.S.I. circuit, implemented in TTL (with the active outputs on 0) and CMOS (with the active outputs on 1) technology.

Generally, these integrate circuits are 4-byte decoders.

*The binary-decimal decoder*



*Fig. 3 The block diagram*

The working of the circuit can be briefly described in the truth table (Table 1):

**Table 1**

No.	D	C	B	A	Active outputs	Active outputs
0	0	0	0	0	y <sub>0</sub>	y <sub>0</sub>
1	0	0	0	1	y <sub>1</sub>	y <sub>1</sub>
2	0	0	1	0	y <sub>2</sub>	y <sub>2</sub>
3	0	0	1	1	y <sub>3</sub>	y <sub>3</sub>
4	0	1	0	0	y <sub>4</sub>	y <sub>4</sub>
5	0	1	0	1	y <sub>5</sub>	y <sub>5</sub>
6	0	1	1	0	y <sub>6</sub>	y <sub>6</sub>
7	0	1	1	1	y <sub>7</sub>	y <sub>7</sub>
8	1	0	0	0	y <sub>8</sub>	y <sub>8</sub>
9	1	0	0	1	y <sub>9</sub>	y <sub>9</sub>
10	1	0	1	0	y <sub>10</sub>	-
11	1	0	1	1	y <sub>11</sub>	-
12	1	1	0	0	y <sub>12</sub>	-
13	1	1	0	1	y <sub>13</sub>	-
14	1	1	1	0	y <sub>14</sub>	-
15	1	1	1	1	y <sub>15</sub>	-

The decoder can identify by its outputs any combination of inputs. The binary-decimal decoders can be used for the implementation of logical functions, but they can especially be found in the memory circuits, for the selection of the cells addressed at a certain time. They can also be used for the selection of the memory circuits and input-output circuits within the systems with  $\mu P$ .

The decoding was carried out by means of 4 decoders. The four binary-decimal decoders (ic1-ic4) achieve a complete decoding of the address space reserved to the ports, using the SA9-SA0 and AEN, IORC, IOWC signals (table 2).

**Table 2**

AEN	SP1			SP2			SP3			SA0	IOWC	IORC	DESCRIPTION
	SA 9	SA8	SA7	SA6	SA5	SA4	SA3	SA2	SA1				
1	X	X	X	X	X	X	X	X	X	X	X	X	-
0	X	X	X	X	X	X	X	X	X	X	X	X	-
										0	0	1	PA
										1	0	1	PB
										0	1	0	PC
										1	1	0	PD
										X	1	1	IMPOSSIBLE
	0 – 34			0 – Fh			0 - Fh						

In order to assign the port addresses, 340h- 341h for example, the JP1- JP3 jumpers must be set as it follows:

JP1	JP2	JP3
X → 6	Y → 3	Z → 0

### **3. CONCLUSIONS**

This work carried out the study of the board that will be connected to the ISA bus of the computer. This board was built and its functioning was tested by means of a program that represents a four non-multiplexed display-cell decimal counter.

### **4. REFERENCES**

1. Poantă, A., Sisteme cu microprocesor, Note de curs
2. Lupu Stăncescu, Microprocesoare. Circuite. Proiectare, Editura Militară, București, 1986